PISNEER!

QUANTUM Fresh

Ductless Wall Mount Split Systems

24 SEER Ultra High Efficiency

Heat Pump + DC Inverter in One System

Single Zone 12000 BTU/hr

208V~230V, 60Hz, 1Ph

Wireless Access Via Free Smartphone App



















DC INVERTER HEAT PUMP






























Whisper-Ouiet Operation



Dual Drain



Display



Maintenance



Eco-Friendly Refrigerant



Customizable



Soft Breeze



3D Air Fow



Power Loss Ultra-Thin Design **Memory Recovery**



Rapid Delivery Output



Energy Saving



STANDARD FEATURES

- Digital Backlit LED Display On Front Panel
- Designed For Standard Wall Hung Installation
- Reverse Cycle / Heat Pump Application Latest Design Attractive Acrylic Flat Panel
- Full ABS Plastic Casing for Indoor Units
- Removable Flip Open Style Front Panel Cover
- Washable Return Air Filter Cartridges
- Self Learning Time-Demand Defrost Logic Automatic Synchronized Discharge Louver
- Three + Auto Speed Digital EC-DC Blower Motor
- Digital Motor Speed Control System
- Whisper Quiet Indoor Motor with Ball Bearings
- High Air Flow Volume for Quick Performance Ultra High Efficiency Grooved Copper Tubes

- Enhanced Louvered Hydrophilic Aluminum Fins
- Superior Efficiency Rating Under Variety of Conditions
- Dynamically Balanced Ultra Quiet Cross-Flow Blower Anti Mildew Treatment on Blower Wheels
- Internal Noise and Vibration Isolation
- High Output & Quiet Variable Speed Compressors
- Very Low Starting Current
- Anti Discoloration Formulated Plastic Dves
- Low Ambient Condenser Heat Strip for -13°F Heating
- LCD Screen Infrared Electronic Control
- Auto-Restart with Memory for Power Outages
- Timer for Preset Starting and Stopping Auto Changeover, Dry and Fan Only Modes
- Season Sensitive Operational Logic

- Large Capacity Suction Accumulators
- Ultra Galvanized Sheet Metal Parts
- Heavy Coat of Baked Enamel Paint for the Outdoor Unit
- Durable Outdoor Fan with High Glass Content
- Efficient, Permanently Lubricated EC-DC Outdoor Motor
- Internal Overload Protection for Motors
- Flare Type Refrigerant Connections
- Full Operating Charge of Refrigerant (R454B)
- Standardized Cabinet Design for all Models
- Piping and Wiring Through Bottom, Sides or Rear of Unit
- Highest Grade Components for Long Life Expectancy
- Ample Availability of Spare Parts and Accessories Wireless Access Via Free Smartphone App Included
- Built to Withstand Extreme Ambient Climates

Full System Model Number			WYT012GLUI25FV
no	Indoor Unit Model Number		WT012GLUI25FVQ
energy DO OP	Indoor Unit Model Code		Z1U20102001189
	Outdoor Unit Model Number		YN012GLUI25RPQ
ENERGY STAR	Outdoor Unit Model Code		Z1U20103001028
System Type			QUANTUM FRESH Series High Wall Mount Type Split Heat Pump System (SEER2 24)
Modes			Cooling, Heating, Dehumidification, Ventilation, with selectable 10% FRESH AIR intake
Control type			Standard set with IR wireless remote (Other optional controllers are available)
Input power supply			208~230V~/60Hz/1P
Power supply range			187~253 VAC
Energy Star Rating			✓
NEEP Rating			✓
Cooling performance	Rated cooling capacity (at 95°F)	Btu/h	12,000
	Cooling capacity range	Btu/h	3,000~15,000
	EER2 Rating	Btu/W.h	13
	SEER2 Rating	Btu/W.h	24
Heating performance	Rated Heating capacity (at 47°F)	Btu/h	13,100
	Rated Heating capacity (at 17°F)	Btu/h	8,000
	Heating capacity range	Btu/h	3,000~13,600
	HSPF2 Rating (Region IV)	Btu/W.h	9.5
	HSPF2 Rating (Region V)	Btu/W.h	8.5
	COP2 (at 47°F)	W/W	4.2
	Max. Heating capacity (at 5°F)	Btu/h	10,100
	Performance percentage		77%
	COP2 (at 5°F)	W/W	2.0
	Max. Heating capcacity (at -4°F)	Btu/h	7600.0
Rated power	Cooling	W	930
consumption	Heating	W	910
Rated power current	Cooling	Α	4.4
	Heating	Α	4.2
Min. circuit ampacity		Α	11
Max. circuit breaker		Α .	15
Moisture removal		Pint/day	65
	Туре	1.	R32 (A2L rated refrigerant with a lower GWP rating of 675)
Refrigerant and room size specifications	Amount	Ozs	22.2
	Sufficiency for max line set length	Ft	25
	Adjustment amount per feet	Ozs	0.11
	Recommended room size	Sq.Ft	350~500
	Minimum room size (unit height 6')	SqF	25
Air volume and sound	Turbo/High/Med/Low/Mute	CFM	440/410/380/230/150
level	(Fresh air volume: 18 CFM)	dB(A)	44/43/37/32/30
Outdoor sound	lc	dB(A)	53
	Gas Liquid	In (OD) In (OD)	3/8" 1/4"
Connecting pipe	Accessory line set length available	Feet	1/4 10' / 16' / 25' / 33' / 50' (can be further extended using coupling kits). Both Standard copper and fully flexible sets are available
	Maximum allowable length	Feet	10 / 16 / 25 / 33 / 50 (can be further extended using coupling kits). Both Standard copper and fully flexible sets are available
	Maximum allowable length		33
	Net unit dimensions (WxDxH)	Feet Inch	36"-1/4 x 12"-1/4 x 8"-1/8
	Carton box dimensions (WxDxH)	Inch	30 -1/4×12 -1/4×6 -1/8 39"-1/4×15"-1/4×12"-1/4
Indoor unit dimensions	Shipping factor	men	0.0017
and weight	Net unit weight	Lbs	25.4
	Shipping weight	Lbs	32.2
Outdoor unit dimensions and weight	Net unit dimensions (WxDxH)	Inch	31"-7/8 x 12" x 21"-5/8
	Carton box dimensions (WxDxH)	Inch	31 -1/0 x 12 x 14 - 3/8 33"-1/2 x 14"-1/8 x 23"-5/8
	Shipping factor	men	0.00294
		Lbs	55.1
	Net unit weight Shipping weight	Lbs	55.1 61.7
Connecting cable	Durbhus meight	LUS	AWG #16 x 4 Core TC-ER cable
Temperature setting range		°F	62 ~ 86
Working ambient temperature range for cooling		°F	5~122
Working ambient temperature range for heating		°F	-4~86
Rated cooling performance data is based on standard ARI conditions of 80°F-DB/67°F-WB Indoor and 95°F Outdoor ambient conditions. Rated heating performance data is based on standard ARI conditions of 70°F-DB/60°F-WB Indoor and 95°F Outdoor ambient conditions. Variable speed inverter systems adjust their output capacity automatically based on actual indoor and outdoor			

Rated cooling performance data is based on standard ARI conditions of 80°F-DB/67°F-WB Indoor and 95°F Outdoor ambient conditions. Rated heating performance data is based on standard ARI conditions of 70°F-DB/67°F-WB Indoor and 47°F Outdoor ambient conditions. Variable speed inverter systems adjust their output capacity automatically based on actual indoor and outdoor atmemperatures, thermostal stettings and other heating or cooling loads. Capacity of the system output and related power input and installation height of minimum of feet from the floor level. Lower levels require larger min. room sizes. Specifications and data listed herein are subject to change without notice due to constant product and engineering improvements. Always refer to the equipment nameplate for applicable exact information.